

Soft-Mount Washer-Extractors AWWA028



Model No.		AWWA028	
Load Capacity Guide	Bed Sheet (Single)	26	
	Lab Coat / Uniform	53	
	Shirt	95	
	Pajamas	44	
	Washcloth	1050	
	Blanket	7	
Capacity(kg)		28	
Control Interface		Touchscreen	
Electric Heater		-	V
Heater Size(kW)		-	20
Drum Dimension		890 Ø × 461mm	890 Ø × 461mm
Drum Speed	Wash (rpm)	20 - 50	20 - 50
	Extract (rpm)	100 - 800	100 - 800
Electrical Requirement OCPD Rating (A)	AC415V/50-60Hz/3Ph	20	50
Motor Size(kW/P)		5.5/4	5.5/4
Connection Port(in.) Pressure(MPa)	Cold Water Supply	Rc1(0.1 - 0.3)	Rc1(0.1 - 0.3)
	Hot Water Supply	Rc1(0.1 - 0.3)	Rc1(0.1 - 0.3)
	Detergent Cup Water	Rc1/2(0.1 - 0.3)	Rc1/2(0.1 - 0.3)
	Water Drain	G2•1/2	G2•1/2
	Steam	◎Rc1/2(0.4 - 0.6)	-
	Compressed-Air	-	-
Water Level (L)		36 - 199	36 - 199
Machine Dimensions (mm)(W × D × H)		1143 × 1255 × 1714	1143 × 1255 × 1714
Weight(kg)		850	850
Detergent Cup (psc)		2	2
Chemical Injection Ports psc (Max. psc)		8(8)	8(8)
Chemical Injection Pump psc (Max. psc)		◎0(8)	◎0(8)
Drum Gap Guard		◎	◎
Water Reclamation System		◎	◎

*◎ = Optional

