

Washer-dryer combo AWDU035




Model No.		AWDU035
Load Capacity Guide	Bed Sheet (Single)	18
	Lab Coat / Uniform	35
	Shirt	64
	Pajamas	29
	Washcloth	700
	Blanket	5
Capacity(kg) Washer extractor/Tumble dryer		35.2/15
Control Interface		Touchscreen
Drum Dimension(mm)		890 Ø × 566mm
Drum Speed	Wash (rpm)	20 - 50
	Extract (rpm)	100 - 800
Electrical Requirement OCPD Rating (A)	AC380-415V/50-60Hz/3Ph	20
Motor Size(kW/P) / (HP)		5.5/4
Heating System Of Wash		Hot Water Supply & Steam
Heating System Of The Dryer		Steam
Connection Port(in.) Pressure(MPa)	Cold Water Supply	Rc1(0.1 - 0.3)
	Hot Water Supply	Rc1(0.1 - 0.3)
	Detergent Cup Water	Rc1/2(0.1 - 0.3)
	Water Drain	G2•1/2
	Heating Steam (Supply/Drain)	Rc1/2(0.5 - 0.7)/ Rc3/8(0.5 - 0.7)
	Dryer Steam (Supply/Drain)	Rc1/2(0.5 - 0.7)/ Rc1/2(0.5 - 0.7)
	Duct Diameter	Ø 200mm
Water Level (L)		40 - 224
Gas Consumption (MJ/h)		-
Steam Consumption (kg/H)		45
Machine Dimensions (mm)(W × D × H)		1145 × 1449 × 1980
Weight (kg)		1140
Soap Cups (psc)		2
Chemical Injection Ports psc (Max. psc)		8(8)
Chemical Injection Pump psc (Max. psc)		◎1(8)
Drum Gap Guard		◎

*◎ = Optional

External view

AWDU035



The machine installation bed channel

